### **FINAL REPORT**

CERTIFICATE No.: 25927



Boral Cement Limited
ABN 62 008 528 523
Taylor Avenue New Berrima NSW 2577
Locked Bag 4 New Berrima NSW 2577
T +61 2 4860 2222

TEST CERTIFICATE OF: Maldon Daily Despatch Environment

**PRODUCED AT:** Boral Cement Limited Maldon

**TESTED AT:** Berrima Works Laboratory

**SAMPLE IDENTIFICATION:** MDDNM2401324

**DATE DESPATCHED:** 4/2/2024

PROPERTY	REQUIREMENTS OF AS 3582.2	RESULT
Insoluble Residue (AS 3583.14)		0.4 %
LOI (AS 3583.3)		-1.0 %
SO <sub>3</sub> (AS 2350.2; TM 10.01.07)		0.2 %
MgO (AS 2350.2)	≤ 15.0 %	5.4 %
Al <sub>2</sub> O <sub>3</sub> (AS 2350.2)	≤ 18.0 %	13.0 %
Fe <sub>2</sub> O <sub>3</sub> (AS 2350.2) expressed as FeO *		1.2 % 1.1 %
Mn <sub>2</sub> O <sub>3</sub> (AS 2350.2) expressed as MnO *		0.4 % 0.4 %
Total Alkali (AS 2350.2)		0.4 %
CI (AS 2350.2)	≤ 0.1 %	< 0.01 %
Fineness passing 45μm sieve (AS 3583.1)		98 %
Fineness Index (AS/NZS 2350.8)		385 m <sup>2</sup> /kg

### **REMARKS**

Sampling not carried out by laboratory. Samples tested as received and results only relate to the item tested.

\* NATA accreditation does not cover the performance of this service.

NATA

Accredited for compliance with ISO/IEC 17025 - Testing

Jason Nairn National Technical Manager

NATA Accreditation Number: 530 / 531

Page 1 of 1

Date of Issue: 5/30/2024



# Page 1 of 1 Report Template - Rev. (3) Jul 2021 Authorised by M. A.

# **Boral Construction Materials**

Materials Technical Services

Unit 4, 3–5 Gibbon Road, Baulkham Hills NSW 2153 Australia PO Box 400, Winston Hills NSW 2153

> T +61 (02) 9624 9900 **boral.com.au**

# TEST REPORT - MILLED SLAG

CLIENT:

BORAL CEMENT - MALDON CEMENT

FILE NO: 50/24

ADDRESS:

Maldon Bridge Road, Maldon, NSW 2571

**REQUEST NO: 111496** 

**LAB SAMPLE NO: 300960** 

SOURCE OF SAMPLE: Maldon

**DATE RECEIVED:** 04/04/2024

**SAMPLE IDENTIFICATION:** Environment ID # MDDNM2401324 - w/e 06/04/2024 - Date sampled: 02/04/2024

IDENTIFICATION OF CEMENT USED: Boral Cement SL Berrima Ref. 2022

**TEST METHOD: AS 3583:** Methods of test for supplementary cementitious materials for use with Portland cement

PROPERTY	TEST METHOD	RESULT	DATE TESTED
Relative density Relative water requirement Relative strength 7 days (accelerated) Relative strength 28 days (standard)	AS 3583.5	2.93	06/04/2024
	AS 3583.6	99%	11/04/2024
	AS 3583.6	115%	18/04/2024
	AS 3583.6	112%	09/05/2024

Parisa Sowti, Violeta Paicu, Brad Vanderburg, Jason Nairn, Melody Mancenido, Mat File, File

Note:

Sample supplied by the client and tested as received.

Approved signatory

Serial no.

Sam El-Hamawi

CEM111496.SE.1





# Page 1 of 1 Report Template - Rev. (3) July 2021 - Authorised by M.A.

**Boral Construction Materials** 

Materials Technical Services

Unit 4, 3-5 Gibbon Road, Baulkham Hills NSW 2153 Australia PO Box 400. Winston Hills NSW 2153

> T +61 (02) 9624 9900 boral.com.au

# **TEST REPORT**

CLIENT:

BORAL CEMENT - MALDON CEMENT

Maldon Bridge Road, Maldon, NSW 2571.

PROJECT: Testing of Maldon Environment Sample.

FILE No.:50 / 24

REQUEST No.: 111496

TEST PROCEDURE: AS 3583.7 – Determination of Sulfide Sulfur content

Laboratory Sample No.:

300960

Date Sampled:

02/04/2024

Date Received:

04/04/2024

Date Tested:

29/04/2024

Sample Description:

Enviroment

ID # MDDNM2401324

Field No.:

# **TEST RESULTS:**

Sulfide Sulfur as S (%)

0.34

- Sample was provided by the Client.
- Test results in this test report relate only to the sample tested.
- This report shall not be reproduced except in full without the approval of the Boral MTS Laboratory.

30th April 2024.

Parisa Sowti, Violeta Paicu, Brad Vanderburg, Jason Nairn, Melody Mancenido, Mat.File, File.